

Cennik detaliczny kabli VOVOX, styczeń 2013

		S = zbalansowany	A = niezbalansowany	D = cyfrowy
Jak czytać oznaczenia kabli	Protect = ekranowany	Protect S – zbalansowany kabel ekranowany	Protect A – niezbalansowany kabel ekranowany	
	Direct = nieekranowany	Direct S – zbalansowany kabel nieekranowany		

VOVOX® link	The cables of the VOVOX® link series are the basis of our product line for musicians and recording studios. Very successful already for several years, they establish the excellent reputation of VOVOX. The specific design of the cables and the use of selected, very pure raw materials provide an optimal transmission of audio signals.
VOVOX® link protect A	The multi-purpose sound conductor for transmission of unbalanced signals. Whether live on stage or in the recording studio, this is the perfect cable to transmit unbalanced signals, i.e. for all electrically amplified musical instruments such as electrical guitar, bass, E-piano or keyboards. Also great for acoustic instruments with pickup systems or as a patch cable. Patch - The optimal solution for effect pedals, pedal boards or effects racks. Balanced sound conductor built without compromise and therefore without screen. Perfectly suited for all balanced signals, unaffected whether it's on line- or microphone-level.
VOVOX® link direct S	Since the sound conductor is not shielded , a small risk of interference must be taken in consideration. We suggest to use 'protect' sound conductors when interference will necessarily lead to an uncontrollable situation, e.g. for live concerts or live recordings. For all other applications, VOVOX® link direct S is the perfect choice.
VOVOX® link protect S	Shielded, balanced sound conductor with optimal noise protection. Offers optimal sound quality for situations in which absolutely no risk of interference can be taken.
VOVOX® link direct SD	Balanced, unshielded 110 ohm digital cable. The optimal choice for AES/EBU interconnections.
VOVOX® link protect AD	Unbalanced, shielded digital cable with an impedance of 75 Ohm. Depending on the choice of connectors, it can be used for different data formats such as S/P-DIF, MADI or Wordclock.
VOVOX® drive Speaker Cable	VOVOX® drive speaker cables are specifically built to connect guitar or bass amplifier heads with speaker cabinets. Based on the VOVOX typical solid-core technology, they provide powerful, clear and lively sound.
VOVOX® mucolink direct SD	A very versatile cable, offering excellent results in case of both analog and digital audio signals. It transmits either 8 balanced analog channels or, depending on the transfer rate, 8 – 16 digital channels according to AES/EBU.
VOVOX® mucolink direct S8	Analog multipair cable without shielding for use in high-end recording studios. It combines 8 balanced channels offering uncompromising sound quality and is therefore non-shielded. A small risk of interference must be taken into consideration. In recording studios this risk is limited and in most cases not critical. For live recording the shielded version VOVOX® mucolink protect S8 is recommended.
VOVOX® mucolink protect S8	Shielded multicore sound conductor with 8 balanced channels. The shielding is separated from the ground conductors. It is directly connected to earth with a separate cable.
VOVOX® sonorus	With respect to sound quality, we don't want to make any compromises. This is our credo since the founding of VOVOX. Well-directed research combined with the experience of many years brought us to VOVOX sonorus. This cutting-edge conductor technology offers further enhancement of the quality achieved in transmitting audio signals. VOVOX sonorus: The new reference.
VOVOX® sonorus protect A	As a result of both ingenious construction and the purity of its raw materials VOVOX® sonorus protect A offers unmatched sound quality. This is the perfect cable for all electrically amplified musical instruments such as electrical guitar, bass, E-piano or keyboards. Also great for acoustic instruments with pickup systems or as a patch cable.
VOVOX® sonorus direct S	VOVOX® sonorus direct S is the result of long experience and countless tests. An unmatched resolution is achieved thanks to the elaborate design of this sound conductor. The excellence in transmitting subtle details regarding spatial imaging, offset in depth and harmonics is incredibly impressive. VOVOX® sonorus direct S is an uncompromising, non-shielded cable. A small risk of interference must be taken into consideration.
VOVOX® sonorus drive	VOVOX® sonorus drive is our top-of-the-line speaker cable to connect guitar or bass amplifier heads with speaker cabinets. Thanks to the special cable design and the wide conductor spacing it transmits amplified signals with a maximum of punch and definition.
VOVOX® sonorus muco	VOVOX® sonorus muco combines eight balanced, non-shielded channels to a multipair cable in the most uncompromising way. If the result wasn't that convincing, we wouldn't produce this special cable: The assembling is truly intricate and demands a lot of experience. This is an example of excellent Swiss craftsmanship for perfect sound quality in recording and mastering studios.
VOVOX® initio power	High end, hi-fi enthusiasts take it as gospel, but sound and electrical engineers take it as snake-oil: that power cords have an influence on the sound quality of audio components. Even for us, it took some time to convince us of the importance of power cords. However, what we listened, we discovered much more than we had counted on! VOVOX® initio power is a power cable for connecting audio components to 110 V / 230 V mains voltage. It is based on the same principals using the same premium quality materials as all VOVOX sound conductors. It is non-shielded and doesn't contain any line filters.

Instrument and Patch Cable VOVOX® link protect A

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.0701	30 / 1	phone plug	phone plug	170
6.0702	100 / 3.3	phone plug	phone plug	210
6.0703	350 / 11.5	phone plug	phone plug	350
6.0704	600 / 19.7	phone plug	phone plug	470
6.0705	900 / 29.6	phone plug	phone plug	630
6.0706	30 / 1	angled phone plug	angled phone plug	170
6.0707	350 / 11.5	angled phone plug	phone plug	350
6.0708	600 / 19.7	angled phone plug	phone plug	470
6.0709	900 / 29.6	angled phone plug	phone plug	630

Interconnect Cable VOVOX® link protect A

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.0710	2 x 100 / 2 x 3.3	RCA	RCA	450
6.0711	2 x 200 / 2 x 6.6	RCA	RCA	560
6.0712	2 x 350 / 2 x 11.5	RCA	RCA	710

Non-shielded Balanced Cable VOVOX® link direct S

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.0901	100 / 3.3	XLR female	XLR male	210
6.0913	100 / 3.3	TRS	XLR male	210
6.0914	100 / 3.3	XLR female	TRS	210
6.0915	100 / 3.3	TRS	TRS	210
6.0909	200 / 6.6	XLR female	XLR male	260
6.0910	200 / 6.6	TRS	XLR male	260
6.0916	200 / 6.6	XLR female	TRS	260
6.0917	200 / 6.6	TRS	TRS	260
6.0902	350 / 11.5	XLR female	XLR male	330
6.0911	350 / 11.5	TRS	XLR male	330
6.0918	350 / 11.5	XLR female	TRS	330
6.0919	350 / 11.5	TRS	TRS	330
6.0903	500 / 16.4	XLR female	XLR male	410
6.0912	500 / 16.4	TRS	XLR male	410
6.0904	750 / 24.6	XLR female	XLR male	530
6.0905	1000 / 32.8	XLR female	XLR male	650
6.0906	2 x 500 / 2 x 16.4 matched	XLR female	XLR male	850
6.0907	2 x 750 / 2 x 24.6 matched	XLR female	XLR male	1090
6.0908	2 x 1000 / 2 x 32.8 matched	XLR female	XLR male	1340

Shielded Balanced Cable VOVOX® link protect S

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.1001	100 / 3.3	XLR female	XLR male	250
6.1013	100 / 3.3	TRS	XLR male	250
6.1014	100 / 3.3	XLR female	TRS	250
6.1015	100 / 3.3	TRS	TRS	250
6.1009	200 / 6.6	XLR female	XLR male	320
6.1010	200 / 6.6	TRS	XLR male	320
6.1016	200 / 6.6	XLR female	TRS	320
6.1017	200 / 6.6	TRS	TRS	320
6.1002	350 / 11.5	XLR female	XLR male	440
6.1011	350 / 11.5	TRS	XLR male	440
6.1018	350 / 11.5	XLR female	TRS	440
6.1019	350 / 11.5	TRS	TRS	440
6.1003	500 / 16.4	XLR female	XLR male	550
6.1012	500 / 16.4	TRS	XLR male	550
6.1004	750 / 24.6	XLR female	XLR male	730
6.1005	1000 / 32.8	XLR female	XLR male	920
6.1006	2 x 500 / 2 x 16.4 matched	XLR female	XLR male	1140
6.1007	2 x 750 / 2 x 24.6 matched	XLR female	XLR male	1510
6.1008	2 x 1000 / 2 x 32.8 matched	XLR female	XLR male	1870

AES/EBU Cable VOVOX® link direct SD

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.2001	100 / 3.3	XLR female	XLR male	190
6.2002	200 / 6.6	XLR female	XLR male	230
6.2003	350 / 11.5	XLR female	XLR male	300
6.2004	500 / 16.4	XLR female	XLR male	370
6.2005	750 / 24.6	XLR female	XLR male	490
6.2006	1000 / 32.8	XLR female	XLR male	600

Audiotech

Biuro i Studio Odsluchowe, ul. Łagiewnicka 20 (wejście od ul. Muzycznej), 02-860 Warszawa,
tel: (22) 648 29 35, www.audiotechpro.pl, e-mail: info@audiotechpro.pl

S/P-DIF Cable VOVOX® link protect AD

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.2101	100 / 3.3	RCA	RCA	240
6.2102	200 / 6.6	RCA	RCA	300
6.2103	350 / 11.5	RCA	RCA	400
6.2104	500 / 16.4	RCA	RCA	490
6.2105	750 / 24.6	RCA	RCA	650
6.2106	1000 / 32.8	RCA	RCA	810

Wordclock Cable VOVOX® link protect AD

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.2107	100 / 3.3	BNC	BNC	300
6.2108	200 / 6.6	BNC	BNC	370
6.2109	350 / 11.5	BNC	BNC	460
6.2110	500 / 16.4	BNC	BNC	560
6.2111	750 / 24.6	BNC	BNC	720
6.2112	1000 / 32.8	BNC	BNC	880

Speaker Cable VOVOX® drive

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.1401	100 / 3.3	phone plug	phone plug	210
6.1403	100 / 3.3	Speakon	Speakon	210
6.1402	200 / 6.6	phone plug	phone plug	280
6.1404	200 / 6.6	Speakon	Speakon	280

Multipair Cable VOVOX® mucolink direct SD

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.2201	100 / 3.3	bi-direc	DB25	960
6.2202	100 / 3.3		DB25	1210
6.2203	100 / 3.3		8xXLRf	1210
6.2204	100 / 3.3	bi-direc	DB25	1250
6.2205	200 / 6.6	bi-direc	DB25	1230
6.2206	200 / 6.6		DB25	1480
6.2207	200 / 6.6		8xXLRf	1480
6.2208	200 / 6.6	bi-direc	DB25	1520
6.2209	300 / 6.6	bi-direc	DB25	1510
6.2210	300 / 9.9		DB25	1760
6.2211	300 / 9.9		8xXLRf	1760
6.2212	300 / 6.6	bi-direc	DB25	1800
6.2213	300 / 9.9		8xXLRf	1890

Pinologia standardowa: Tascam / inna pinologia: skontaktuj się z Audiotech

Multipair Cable VOVOX® mucolink direct S8

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.1601	100 / 3.3		DB25	1260
6.1602	100 / 3.3		DB25	1510
6.1603	100 / 3.3		8xXLRf	1510
6.1605	200 / 6.6		DB25	1620
6.1606	200 / 6.6		DB25	1870
6.1607	200 / 6.6		8xXLRf	1870
6.1609	300 / 9.9		DB25	2010
6.1610	300 / 9.9		DB25	2240
6.1611	300 / 9.9		8xXLRf	2240
6.1612	300 / 9.9		8xXLRf	2350

Pinologia standardowa: Tascam / inna pinologia: skontaktuj się z Audiotech

Multipair Cable VOVOX® mucolink protect S8

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.1701	100 / 3.3		DB25	1500
6.1702	100 / 3.3		DB25	1740
6.1703	100 / 3.3		8xXLRf	1740
6.1705	200 / 6.6		DB25	2050
6.1706	200 / 6.6		DB25	2300
6.1707	200 / 6.6		8xXLRf	2300
6.1709	300 / 9.9		DB25	2610
6.1710	300 / 9.9		DB25	2850
6.1711	300 / 9.9		8xXLRf	2850
6.1713	300 / 9.9		8xXLRf	2960

Pinologia standardowa: Tascam / inna pinologia: skontaktuj się z Audiotech

Audiotech

Biurowisko i Studio Odsluchowe, ul. Łagiewnicka 20 (wejście od ul. Muzycznej), 02-860 Warszawa,
tel: (22) 648 29 35, www.audiotechpro.pl, e-mail: info@audiotechpro.pl

Instrument and Patch Cable VOVOX® sonorus protect A

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.3201	30 / 1	phone plug	phone plug	180
6.3202	100 / 3.3	phone plug	phone plug	230
6.3203	350 / 11.5	phone plug	phone plug	430
6.3204	600 / 19.7	phone plug	phone plug	620
6.3206	30 / 1	angled phone plug	angled phone plug	180
6.3207	350 / 11.5	angled phone plug	phone plug	430
6.3208	600 / 19.7	angled phone plug	phone plug	620

Stereo Instrument Cable VOVOX® sonorus protect A twin

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.3601	350 / 11.5	stereo phone plug	2 x phone plug	710
6.3602	350 / 11.5	angled stereo phone plug	2 x phone plug	710
6.3603	600 / 19.7	stereo phone plug	2 x phone plug	1030
6.3604	600 / 19.7	angled stereo phone plug	2 x phone plug	1030

Non-shielded Balanced Cable VOVOX® sonorus direct S

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.3301	100 / 3.3	XLR female	XLR male	250
6.3313	100 / 3.3	TRS	XLR male	250
6.3314	100 / 3.3	XLR female	TRS	250
6.3315	100 / 3.3	TRS	TRS	250
6.3309	200 / 6.6	XLR female	XLR male	320
6.3310	200 / 6.6	TRS	XLR male	320
6.3316	200 / 6.6	XLR female	TRS	320
6.3317	200 / 6.6	TRS	TRS	320
6.3302	350 / 11.5	XLR female	XLR male	440
6.3311	350 / 11.5	TRS	XLR male	440
6.3318	350 / 11.5	XLR female	TRS	440
6.3319	350 / 11.5	TRS	TRS	440
6.3303	500 / 16.4	XLR female	XLR male	560
6.3312	500 / 16.4	TRS	XLR male	560
6.3304	750 / 24.6	XLR female	XLR male	750
6.3305	1000 / 32.8	XLR female	XLR male	940
6.3306	2 x 500 / 2 x 16.4 matched	XLR female	XLR male	1150
6.3307	2 x 750 / 2 x 24.6 matched	XLR female	XLR male	1540
6.3308	2 x 1000 / 2 x 32.8 matched	XLR female	XLR male	1920

Speaker Cable VOVOX® sonorus drive

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.3501	100 / 3.3	phone plug	phone plug	260
6.3503	100 / 3.3	Speakon	Speakon	260
6.3502	200 / 6.6	phone plug	phone plug	360
6.3504	200 / 6.6	Speakon	Speakon	360

Multipair Cable VOVOX® sonorus muco

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
6.3401	100 / 3.3	DB25	DB25	1640
6.3402	100 / 3.3	DB25	8xXLRm	1810
6.3403	100 / 3.3	8xXLRf	DB25	1810
6.3405	200 / 6.6	DB25	DB25	2250
6.3406	200 / 6.6	DB25	8xXLRm	2440
6.3407	200 / 6.6	8xXLRf	DB25	2440
6.3409	300 / 9.9	DB25	DB25	2860
6.3410	300 / 9.9	DB25	8xXLRm	3040
6.3411	300 / 9.9	8xXLRf	DB25	3040
6.3413	300 / 9.9	8xXLRf	8xXLRm	3140

Pinologia standardowa: Tascam / inna pinologia: skontaktuj się z Audiotech

Power Cable VOVOX® initio power

Kod produktu	Długość w cm	Wejście	Wyjście	Cena PLN/szt brutto
4.0601	100 / 3.3	SchuKo	IEC	430
4.0602	180 / 5.94	SchuKo	IEC	590
4.0603	100 / 3.3	NEMA 5-15	IEC	530
4.0604	180 / 5.94	NEMA 5-15	IEC	690

Audiotech

Biurowo i Studio Odsluchowe, ul. Łagiewnicka 20 (wejście od ul. Muzycznej), 02-860 Warszawa,
tel: (22) 648 29 35, www.audiotechpro.pl, e-mail: info@audiotechpro.pl